

# **BOWDLER ELECTRIC INC.**

86 Old Ocean House Road  
 Cape Elizabeth, ME 04107  
 (207) 799-5828  
 FAX: 799-6699

# **Proposal**

Date	Proposal #
6/8/2012	4842 - A

NAME / ADDRESS
Josef Chalot Architect 327 Ocean House Rd. Cape Elizabeth, ME 04107

<b>Project</b>		<b>Terms</b>
typical hardwired system		See customer message.
<b>Item</b>	<b>Description</b>	<b>TOTAL</b>
Job requested	1. Cut-in and fish wiring in for a complete hardwired smoke and CO detector system. Estimate produced from plans submitted of a 3 bedroom, 2 story home with a finished basement. Assuming drywall ceiling and walls, clear attic and basement ceiling access. System to have <del>5</del> <b>4</b> smoke and <del>1</del> <b>2</b> combination smoke/CO detectors.	845.00
Job requested	2. Fish power in from attic space, cut in emergency light outlet. Install fixture over stairs. (not including fixture).	225.00
Permit	3. Electrical Permit.	25.00
	Sales Tax	0.00
<i>1/3 down to start, balance @ finish.</i>		
BowdlerElectric.com mbe@maine.rr.com		<b>TOTAL \$1,095.00</b>

**Customer's Acceptance of Proposal**

X \_\_\_\_\_

Bowdler Electric, ... \_\_\_\_\_

Date \_\_\_/\_\_\_/\_\_\_

# EMERGENCY LIGHTING



More saving. More doing.™

[Share](#) [Email](#) [Print](#)

## Lithonia Lighting Quantum 2-Light Emergency Fixture Unit

Model # ELM Internet # 100083144 Store SKU # 295219

(2) [Write a Review](#)

**\$36.86 /EA-Each**

**Ships FREE with \$45.00 Order**

This item cannot be shipped to the following state(s): AK, HI



Zoom

[Product Description](#)

[Specifications](#)

[Customer Reviews](#)

[More Info](#)

[Shipping Options](#)

## PRODUCT DESCRIPTION

The Lithonia Lighting Quantum 2-Light Emergency Fixture Unit has a white, impact-resistant thermoplastic housing and contemporary design. This 2-light emergency fixture is ideal for applications requiring attractive equipment and quick installation.

- Compact design
- White thermoplastic housing
- Quick-mount installation
- UL listed
- Dual voltage
- Uses 2 halogen bulbs (included)
- MFG Brand Name : Lithonia Lighting
- MFG Model # : ELM
- MFG Part # : 383585

[Return To Top](#)

# EMERGENCY LIGHTING

PRODUCT INFORMATION

Architectural

## AFN Affinity®



**Intended Use**

Provides a minimum of 90 minutes illumination for the rated wattage upon loss of AC power. Ideal for applications requiring attractive unit equipment.

**Construction**

Compact, low-profile, architectural design with die-cast aluminum housing. Available finishes are textured polyester powder coat paint in nickel white, black and dark bronze.

The self-diagnostic emergency units comply

with NFPA Life Safety Code® and automatically test the battery once a month for five minutes and once every six months for 30 minutes.

U.S. Patent No. D468,046.

Standard optics provided with two 6W wedge-base xenon lamps offer 55% more light output than standard incandescent lamps.

Forward throw (FWD) option optics provided with two high-brightness white LEDs projecting a forward throw beam of light.

Patented reflector/refractor design features superior vac-metalized, die-casted reflectors and multi-faceted, highly transmissive refractors that significantly improve photometrics.

Maintenance-free lead-calcium battery (standard). Nickel-cadmium optional.

Dual-voltage input capability (120/277V).

Low-profile, integrated test switch/pilot light located below the lens.

Rigid conduit entry provision on top of the unit.

Remote version available for exterior use. Ideal for exit discharge applications.

**Listings**

UL Listed. Meets UL 924. Wet location (EXT) listed. Damp location (PREM, EXT) listed. Cold weather (EXT) listed. Meets NFPA 101, NFPA 70-NEC and OSHA illumination standards.

ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

**Example:** AFN W EXT

Series	Voltage	Finish	Options
AFN	<b>(blank)</b> 120/277V	<b>W</b> White B Black BN Brushed nickel <b>DB</b> Dark bronze <sup>1</sup>	<b>(blank)</b> Lead-calcium battery PREM Nickel-cadmium battery, self-diagnostics and damp location 32° to 122°F (0° to 50°C) <b>EXT</b> High-temperature nickel-cadmium battery listed from 0° to 122°F (-18° to 50°C), time delay, self-diagnostics, damp and wet location FWD Forward throw optics


ADDITIONAL INFORMATION

For additional product information, visit [www.lithonia.com](http://www.lithonia.com).

ELECTRICAL APPLICATION DATA

TYPE	AC INPUT			OUTPUT VOLTS	OUTPUT WATTS 1-1/2 HRS
	VOLTS	AMPS	WATTS		
AFN	120	.11	1.1	6	12
AFN	277	.12	1.3	6	12
AFN PREM	120	.15	1.4	6	12
AFN PREM	277	.14	1.4	6	12
AFN EXT	120	.23	21	6	12
AFN EXT	277	.25	35	6	12

Drawings are for dimensional detail only and may not represent actual mechanical configuration. Dimensions are shown in inches (centimeters) unless otherwise noted.



Weight: 3.5 lbs (1.6 kg)

**Notes**

<sup>1</sup> Dark bronze can only be ordered with EXT. This finish is not available on other units.

For application guidelines and fixture performance data, see page 479.

**\$302. online**





More saving. More doing.™

[Share](#) [Email](#) [Print](#)



Zoom

## Universal Security Instruments 9 Volt Battery Operated Smoke and Carbon Monoxide Alarm

Model # CD-9775 Internet # 100661937.

(2) [Write a Review](#)

**\$29.97 /EA-Each**

**Ships FREE with \$45.00 Order**

This item cannot be shipped to the following state(s): AK, HI

[Product Description](#)

[Specifications](#)

[Customer Reviews](#)

[More Info](#)

[Shipping Options](#)

### PRODUCT DESCRIPTION

The CD-9775 combination smoke & carbon monoxide alarm features different alarm sounds to distinguish between a smoke alarm and a CO alarm. Universal Security battery operated smoke and carbon monoxide alarms are easy to install. For maximum protection, install smoke alarms and carbon monoxide alarms in every sleeping room, and on every level of your home.

- Combination ionization smoke alarm and carbon monoxide alarm--One alarm provides two types of protection
- 9 Volt alkaline battery included
- Front load battery drawer for easy battery replacement
- Audible low battery warning signal
- Test/silence button
- MFG Brand Name : Universal Security Instruments
- MFG Model # : CD-9775
- MFG Part # : CD-9775

[Return To Top](#)

### SPECIFICATIONS

Assembled Depth (in.)	2 in	Assembled Height (in.)	6 in
Assembled Width (in.)	6 in	Battery Back-Up	No
Carbon Monoxide Detector Included	Yes	Commercial/Residential	Residential
Connector/Contact Type	None	Digital Display	No
Electrical Product Type	Carbon Monoxide Detector	Heat Detector Included	No
Returnable	90-Day	Test/Reset Button	Yes
Visible Sensor	No	Voltage (volts)	9 V
Wired or Wireless	Wireless	<b>NOT HARD WIRED</b>	



More saving. More doing.™

[Share](#) [Email](#) [Print](#)



## Kidde Full Home Fire Extinguisher

Model # 21007245 Store SKU # 130577  
Store SO SKU # 198092

(4) [Write a Review](#)

**\$46.00 /EA-Each**

[Zoom](#)

[Product Description](#)

[Specifications](#)

[Customer Reviews](#)

[More Info](#)

[Shipping Options](#)

## PRODUCT DESCRIPTION

Make sure your house, garage and workshop are prepared for potential fires by acquiring the Kidde 3-A:40-B:C Fire Extinguisher. This fire extinguisher is suitable for use on fire involving household materials, including fabrics, plastics, wood, paper, flammable liquids and electrical equipment. This non-rechargeable extinguisher offers a pressure gauge for accurate pressure readings and an easy-pull safety pin that helps to eliminate accidental discharges.

- Kidde UL listed 3-A:40-B:C fire extinguisher is rated for use on household fires
- Pressure gauge allows you to check that the extinguisher is in proper working order
- Rust and impact resistant nylon handle
- Easy-pull safety pin helps prevent accidental discharges
- The Full Home extinguisher has a discharge time of 13-15 seconds, discharge range of 12-18 feet with operating pressure rated at 195 PSI
- MFG Brand Name : Kidde
- MFG Model # : 21007245
- MFG Part # : 21007245

[Return To Top](#)

## SPECIFICATIONS

Assembled Depth (in.)	4.5 in	Assembled Height (in.)	16.07 in
Assembled Width (in.)	7.5 in	Electrical Product Type	Fire Extinguisher
Item Package Type	Cardboard Container	Returnable	90-Day